

SAVE TIME, MONEY, AND SPACE – MAXIMIZE EFFICIENCY

- Multiple applications, combination therapy
- Ergonomic design for ease of operation
- Convenient features for rapid and gentle procedures
- Time efficiency increases the clinic's ROI

SYSTEM SPECIFICATIONS

Wavelength	755 nm / 1064 nm
Laser Type	Long Pulsed Alexandrite / Nd:YAG
Beam Delivery	Lens-coupled Optical Fiber with Handpiece
Aiming Beam	<5 mW @ 532 nm
Pulse Energy (Max. Fluence)	Max 100 J for Nd:YAG Max 55 J for Alexandrite (Max. Fluence 600 J/cm ²)
Pulse Width (ms)	0.35 ms - 300 ms
Pulse Rate (Hz)	0.5 - 10 Hz
Display System	8" Touch LCD GUI
Spot Size (9 types)	2, 3, 5, 8, 10, 12, 15, 18, 20 mm
Emission Control	Finger Switch & Footswitch
Cooling Type	Cryo ICD or Air Cooling
Dimensions (mm)	1148.8 (H), 776.8 (D), 434 (W)
Weight (kg)	110 kg
Electrical rating	4.0 kVA (AC 220 - 230 V, 50/60 Hz)
Calibration	External



Lutronic Corporation

Room 403-1,2,3,4,5, 404 Ilsan Technotown 1141-1, Baeksok-dong, Ilsandong-gu, Goyang-si, Gyeonggi-do, KOREA
TEL. +82-31-908-3440 / FAX. +82-31-907-3440
e-mail. office@lutronic.com

Lutronic Inc. USA

850 Auburn Court Fremont, CA 94538
TEL. +1-888-588-7644

Lutronic Japan Co., Ltd.

9F Hakataekimae Center Bldg., 1-14-16 Hakataekimae, Hakata-ku, Fukuoka city, Fukuoka-pref, 812-0011 Japan
TEL. +81.92.477.2755 / FAX. +81.92.477.2756

Lutronic China

Suite 22, Hyundai Motor Tower, 38 Xiaoyun Road, Chaoyang District, Beijing, CHINA
TEL. +8613910765411

©2012 LUTRONIC Group of Companies. All rights reserved. LUTRONIC, its logo and CLARITY are trademarks or registered trademarks of the LUTRONIC Group of Companies. Specifications are subject to change without notice. This product or the use of this product is covered by one or more U.S. and foreign patents or patent application pending.
CE 0434, P/N 4100147700_v1_A4c

LUTRONIC®



THIS LASER PRODUCT COMPLIES WITH FEDERAL PERFORMANCE STANDARD 21 CFR. 1040.10 AND 1040.11 FOR CLASS IV LASER PRODUCTS